

# PHOENIX™ 1.5



The Phoenix™ 1.5 (NSN: 5855-01-396-8734) is a programmable infrared signaling beacon designed for use as a personnel or vehicle marker during night operations. The operator programs a six second user defined flash pattern via the two programming pins. Miniature indicator lights within the device will flash the pattern as it is being recorded by the user to confirm the code being stored. During operation, the user can reactivate the miniature indicator lights at anytime allowing the operator to confirm the broadcast code in situations where their own night vision equipment has become lost or damaged. The stored program is easily erased by removing and reattaching the battery.

The phoenix 1.5 is available in an infrared (NSN: 5855-01-396-8734), and NV Green or Red (NSN: 5855-01-396-8732) training model.

The Phoenix 1.5 has been utilized by United States Military in a variety of operational theatres such as Kosovo, Bosnia, Somalia, Afghanistan and Iraq.

---

Weight	1 Ounce   28 Grams
Size	1.24" x 0.9" x 0.574"   31mm x 22.5mm x 14.6mm
Flash cycle	6 Seconds
Flash duration	Programmable
Battery	Common 9 volt
Configuration	3 Light Emitting Diodes (LED)
Coverage	240 degrees x 360 degrees
Switching	Attach or remove battery
Options	Phoenix Infrared Beacon (902212IR), Phoenix 1.5 NV Green Training Model (902212G), Phoenix 1.5 Red Training Model (902212R), Vehicle Auxiliary Power Supply (902611), and Poseidon - Phoenix / Pegasus Mounting Clip (902801)
Operating depth	The Poseidon — Phoenix / Pegasus Mounting Clip (902801) provides a water tight casing for the beacon and battery assembly. If immersed without the Poseidon case, the unit will continue to operate until the contacts fail due to water and electrolytic corrosion. Given these conditions the depth limitation is solely determined by the battery's ability to withstand depth.

PHOENIX is a trademark of Cejay Engineering, LLC.

---

ALL INFORMATION INCLUDED IN THIS SPECIFICATION AS WELL AS THE DESIGNED PRODUCT IS SUBJECT TO CHANGE. PLEASE SEE OUR WEB SITE AT [WWW.CEJAYENG.COM](http://WWW.CEJAYENG.COM) FOR THE MOST CURRENT INFORMATION ON OUR PRODUCT SUITE. NO COMPONENT OF THIS PRODUCT OR SPECIFICATION IS AVAILABLE FOR DISTRIBUTION TO ANY PARTY WITHOUT THE EXPRESSED WRITTEN CONSENT OF CEJAY ENGINEERING, LLC

ATTENTION: ANY PRODUCTS USING INFRA RED LIGHT EMISSIONS [850 NM OR ABOVE] REQUIRE STATE DEPARTMENT APPROVAL AND A LICENSE TO EXPORT OUTSIDE THE UNITED STATES.



**Corporate Address:**  
24600 South Tamiami Trail  
Suite 212-353  
Bonita Springs Fl 34134 USA  
Phone & Fax: (888) 584-3060  
Phone & Fax: (239) 349-2336  
E-mail: [info@cejayeng.com](mailto:info@cejayeng.com)

**United Kingdom Address:**  
Suite 102  
St Loyes House  
20 St Loyes Street  
Bedford  
MK40 1ZL  
Tel: 0800 048 8652

Rev Date 4/2010

[www.cejayeng.com](http://www.cejayeng.com)